8x Slim DVD Multi Writer: AD-7710H

- Read speed: DVD 8x max, CD 24x max
- Write speed:
  - DVD+/-R: 8x max
  - DVD+RW: 8x max
  - DVD-RW: 6x max
  - DVD+R9: 6x max
  - DVD-R DL: 6x max
  - DVD-RAM: 5x max
  - CD-R: 24xmax
  - CD-RW: 24x max
- S-ATA interface
- Anti “buffer under run error” system
- 12cm and 8cm CD and DVD media supported
- 160g weight without bezel
- Emergency eject
- Halogen Free

Halogen free

Specifications		8x slimline DVD Multi Writer (AD-7710H)	
		DVD	**CD**
Transfer Rate read (max.)		8x CAV (max. 11000 kByte/s)	24x CAV (max. 3600 kByte/s)
Transfer Rate write	-R	8x CAV (max. 11000 kByte/s)	24x CAV (max. 3600 kByte/s)
	-R DL	6x ZCLV (max. 8300 kByte/s)	./.
	-RW	6x ZCLV (max. 8300 kByte/s)	24x ZCLV (max. 3600 kByte/s)
	-RAM	5x ZCLV (max. 6900 kByte/s)	./.
	+R	8x CAV (max. 11000 kByte/s)	./.
	+R9	6x ZCLV (max. 8300 kByte/s)	./.
	+RW	8x ZCLV (max. 11000 kByte/s)	./.
Access Time		180 ms	150 ms
Mechanism		Tray load mechanism	
Interface		S-ATA	
Burst Tranfer Rate		1.5 Gbps	
Cache Memory		2 MByte	
Media/Modes supported		DVD-ROM, DVD-R(DL), DVD-RW, DVD +R(9), DVD +RW, DVD-Video, CD-ROM, CD-ROM XA, CD-Audio, CD Extra, CD Text, CD-I Ready, CD-Bridge, Photo-CD, VideoCD, Hybrid CD	
Writing methods		DAO (disc at once), SAO (session at once), TAO (track at once) with zero gap, variable or fixed packet, multisession	
Compatibility		MPC Level 3, MultiRead, PC2001, Windows Vista/ Windows 7	
Other features		H = Halogen free, WHQL = 32 & 64bit	
Weight		160 grms	
Dimensions		128mm x 12.7mm x 129mm	
MTBF		80,000 (POH) at 25°C	

Copyright Sony Optiarc Europe GmbH